



GeoVision V8.3.4 Release Notes

New:

- Support for Sanyo IP cameras: VCC-HD2500P, VCC-HD4600 and VCC-HD5600P
- Support for Hikvision IP camera: DS-2CD852MF-E
- Automatic video snapshots triggered by input devices

Fixed:

- **Main System**
 - Issue of recording suspense that occurred when GV-4008 Card detected abnormal video signals
 - Incorrect recording frames with "Limit Video Frame Rate" function enabled
 - Problem of resuming the set screen divisions after a pop-up view in "Quad Spot Monitor Controller" function
 - Several minor issues with "Fast Backup and Restore (FBR)" function
 - Issue of using multiple IP cameras in a low-bandwidth or Internet environment
 - Problem of "Live-View Key Frame Only" function that could not start recording when motion was detected
 - Issue of recording triggered by motion detection from IP devices
- **Remote Applications**
 - Live-image problem from IP devices on the WebCam Server that occurred when dual streams of different video sizes and codecs as well as "Hardware-Compressed Data FIFO" function were applied
 - Connection speed issue of V8.3.3 MultiView when the connection was lower to 512 Kbps

Improved:

- Support for more Vivotek IP cameras: PZ7111, IP8160 and IP7361
- Support for more Arecont IP cameras: 5155DN, AV3155DN, AV2110DN and AV1310DN
- Support for more ACTi IP camera: ACM-5811